

Dot matrix impact printer series using common paper of 57,5±0,5 mm width.

DP24-40: up to 2 copies, 24 or 40 columns.
Internal power supply.
The total access to the printing mechanism and the paper bin allow an easy paper and inked ribbon replacement.
Printing speed up to 80 cps or 10 lines/sec with the fast paper feed system.
An optional mounting kit allows the printer to be fixed to the wall, so that it becomes suitable for the retail/hospitality market as kitchen printer.



Pos Printers

	Dp 24	Dp 40	Dp 24H	Dp 40H
Columns	24	40	24	40
Character/second	60	60	72	80
Lines/second	2,5	1,5	3,2	2,5
Character matrix	6x10			
Printing Method	Impact dot matrix			
Printing direction	Straight or reverse			
Type styles	Normal, double height and width, enlarged			
Character set	ASCII extended			
Paper width	57,5 mm ± 0,5 mm			
Roll dimension	Ø 55 mm max			
Data buffer	192 bytes		1 Kb	
Flash memory	2 Kb (16Kb option)		1 Flash from 16 Kb	
Drivers	Windows™, 98, me, NT4, 2K			
Interfaces	RS 232, Centronics			
Baud rate	From 300 to 9600 bps		From 300 to 38400 bps	
Power Supply	100-240 Vac			
Power consumption	0.2 A			
Reliability MCBF	1.500.500 lines			



DESKTOP PRINTERS

Impact Dot Matrix

Copy Capability

Compact Size

Fast

Convenience & Reliability

